

NOODLE LINK™ LITE (2" mesh - semi privacy)



NOODLE LINK™ LITE is the lightweight member of the Noodle Link family.

This 2" chain link fence has slats and noodles pre-inserted in the chain link mesh at our manufacturing facility, so you do not have to stuff them. **NOODLE LINK™ LITE** uses a flexible round tube to lock the single-wall slats securely in place at both *the top and bottom* of the fence.

NOODLE LINK™ LITE is easy to install, costs less than most other chain link fence systems and it creates a beautifully finished fence your customers will love and appreciate.



2 inch Chain Link Fence with the SLATS and NOODLE locked and Already in the Wire!



NOODLE LINK™ LITE provides approximately 75% or semi-privacy and is available in several wire weights and finishes, slat colors and heights. It also meets ASTM designations, and we guarantee it, too.



"Where Innovation Meets Expectation"



Technical Data

NOODLE LINK™ LITE Specifications	
Single wall slats	✓
Wind load and privacy factor - approximately (Based on wire/mesh used-stretch tension)	75%
2" x 2" Mesh	✓
Manufactured up to 12' high	✓
Available in 9 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 11 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class IV wire (1.20 oz.)	✓
Available in 9 gauge galvanized before weaving (GBW) per ASTM A392 and A817, Type II, class V wire (2.0 oz.)	✓
Available in 9 gauge finish 10 gauge core fused & bonded vinyl coated wire per ASTM F668, class 2B - 7 colors available	✓
Available in 8 gauge finish 9 gauge core fused & bonded vinyl coated wire per ASTM F668, class 2B - 7 colors available	✓
Available in 9 gauge aluminized before weaving wire per ASTM A491, Type 1	✓
Slats meet ASTM F3000 and F3000M designations	✓
Available in a 25' roll 5' minimum increments thereafter	✓
Seven year pro-rata limited warranty	✓

HDPE Technical Properties Available on request.

Installation Instructions

Assemble the frame work, top rail, loop caps, etc.



Insert the needle and connect the rolls same as regular chain link fence. Stand the fence up to the posts and top rail, loosely attach to the top rail, attach tension bar and stretch wire into place. **Do not cut the noodle until you have stretched the wire.**



Install three (3) slats in space between sections.



Cut the excess noodle halfway between the two selvages, so both ends touch and using the hog ring pliers hog ring both ends of the noodle to the wire.

Caution: If you trim the Noodle before stretching the wire, you may end up with not enough Noodle.

Standard Wire Colors



Standard Slat Colors



Colors are approximations. Exact representation of colors is difficult. Please refer to actual color samples for accurate matching. **Samples available upon request.**



YOUR TOTAL FENCING SOURCE

COMMERCIAL, INDUSTRIAL & RESIDENTIAL FENCE PRODUCTS AND ACCESSORIES FOR THE FENCE PROFESSIONAL!